

KUBOTA
SVL65-2



Kubota[®]

BUILDING AUSTRALIA

KUBOTA.COM.AU

COMPACT AND POWERFUL.

Kubota's new SVL65-2 track loader is compact in size yet boasts incredible power, giving you the all-round performance to take on any task.

Model: SVL65-2CH

Cab, Hyd. QC, Std. Flow, Std. Track

Model: SVL65-2CHW

Cab, Hyd. QC, Std. Flow, Wide Track

Model: SVL65-2CHFW

Cab, Hyd. QC, High-Flow, Wide Track

- Powerful Kubota 68 HP engine
- Kubota Vertical Lift to easily dump into trucks or bin
- Standard self-levelling function to keep the bucket or forks level
- Advanced Multifunction Valve (AMV) – Hydraulic system features an innovative AMV that provides smooth movements of all hydraulic functions when operated simultaneously
- Electronic Travel Torque Management – ECU that constantly monitors the load of the machine to optimally control the hyd. pump output, prevents engine stalls for smoother operation
- Strong Bucket Breakout Force (2,093kg)
- Strong Lift Arm Breakout Force (1,935kg)
- Unique sliding front door, can be opened regardless of the position of the bucket or loader arms
- Spacious and comfortable cab
- A/C pressurised cabin
- Suspension seat
- Excellent visibility
- Dial and foot throttle to control engine speed
- Standard Two-speed Travel
- Optional Multi-function levers to provide fingertip control of attachments (Standard on High-flow model)
- Hydraulic Quick Coupler
- Standard Track and Wide Track
- Standard flow 65.8 l/m / High flow 102.2 l/m

Model		SVL65-2	
Type of operator station		Closed CAB	
Engine	Model		V2607-CR-TE4
	Output (SAE J1995 gross)		68.4 HP (51.0kW)/2600rpm
	Output (SAE J1349 net)		59.9 HP (44.7kW)/2600rpm
	Displacement		159.6 cu.in. (2615 cc)
	Cylinders		4
	Bore x Stroke		3.4in. (87mm) x 4.3in. (110mm)
	Aspiration		Turbocharged
Dimensions	Overall height		79.9in. (2029mm)
	Overall length with bucket		136.4in. (3465mm)
	Overall length w/o bucket		107.3in. (2725mm)
	Overall width std. Track / Wide Track		65.2in. (1657mm) / 67.6in. (1717mm)
Loader performance	Rated operating capacity - 35% tipping load		2100lbs. (953kg)
	Tipping load		6000lbs. (2722kg)
	Breakout force	Bucket	4614lbf. (2093kg)
		Lift arm	4266lbf. (1935kg)
Lift arm path		Vertical	
Undercarriage	Track Width	Standard	12.6in. (320mm)
		Wide	15.0in. (380mm)
		Standard	4.9psi
		Wide	4.4psi
	Track rollers (per side)		4
	Track ground contact length		57.9in. (1470mm)
	Travel speed	Low	4.9mph (7.8km/h)
		High	7.1mph (11.5km/h)
Traction force		8406lbf. (3813kgf)	
Min. ground clearance		9.1in. (233mm)	
Hydraulic system	Aux. hydraulic flow	Std. / High Flow	17.4gpm (65.8L/min) / 27.0gpm (102.2L/min)
	Aux. hydraulic pressure		3263psi (229.4kgf/cm ²)
Service refill capacities	Hydraulic system		13.2gal. (50L)
	Hydraulic tank		5.4gal. (20.3L)
	Fuel tank		21.7gal. (82L)
Operating weight (Includes operator weight 165lbs / 75kg)			8465lbs. (3840kg)